

LED A-Frame Specification Sheet

Upgrade your curb appeal with a modern A-frame that turns foot traffic into attention.

Display Specs

Size	43"
Display Area	943x531mm(H*W)
Proportion	9:16
Resolution	1080*1920
Display Color	16.7M
Brightness	1800cd/m ² Satisfy clear image display in strong direct sunlight environment
Contrast Ratio	3500:1
Viewing Angle	178° (H) / 178° (V)
Response Time	5ms
Service Life	60000 hs

System Specs

OS	Android 11
CPU	RK3568, quad core, up to 2.0GHz main frequency
RAM	2G
ROM	32GB
Multimedia (Video)	MPG,AVI,MP4,RM,RMVB,TS
Multimedia (Audio)	MP3,WMA
Multimedia (Image)	JPG,GIF,BMP,PNG

Battery Specs

Charging Time	7 hs
Work Time	10-12 hs
Battery Capacity	50000 mAh
Voltage	24V

Work Environment

Operating Temperature	-25°C ~ 100°C
Storage Temperature	-45°C ~ 80°C
Power Input	AC100V ~ 240V
Power Consumption	≤100W
Standby Power Consumption	≤3W

Appearance

Color	Black
Net Weight	46Kg
Gross Weight	54Kg
Product Dimension	1236mm173mm588mm
Package Size	1370mm310mm700mm



Battery Powered Operation

Built-in battery enables cord-free placement and flexible use throughout the day.

Anti-Glare Tempered Glass

Reduces reflections while adding durability for daily commercial use.

Portable with Locking Bar

Designed for easy relocation with added security to help prevent unwanted movement.

Industrial Casters and Anti-Skid Base

Provides smooth mobility while maintaining stability once positioned.

Ambient Light Sensor

Automatically adjusts brightness based on surrounding light conditions.

Commercial Metal Housing

Durable enclosure designed for frequent use in public environments.