

LED Podium Specification Sheet



| Model | P2.5 (GOB) | P1.8 (GOB) |
|--|-----------------|-----------------|
| Pixel Pitch (mm) | 2.5 | 1.86 |
| Pixel Density | 160000 | 288906 |
| Module Size (W×H×D) | 320×160×5.2mm | 320×160×5.2mm |
| LED Type | SMD1515 | SMD1212 |
| Module Resolution (dots) | 128×64 | 172×86 |
| Module Arrangement (per cabinet) | 6×6 | 6×6 |
| Screen Size (W×H) | 1920×960mm | 1920×960mm |
| Cabinet Size (W×H×D) | 1065×1100×585mm | 1065×1100×585mm |
| Cabinet Weight | 160kg/pc | 160kg/pc |
| Cabinet Resolution (dots) | 768×384 | 1032×516 |
| Scanning Mode | 32/S | 43/S |
| Best Viewing Distance (m) | ≥2.5 | ≥1.86 |
| Brightness | 600Nits | 600Nits |
| Refresh Rate | 3840Hz | 3840Hz |
| Grey Scale | 12-16Bit | 12-16Bit |

Contact Us for Additional Sizes

All-in-One Display Solution

Integrated media playback eliminates the need for external players.

Customizable Content Display

Supports branding, announcements, presentations, lyrics, and messaging.

Wireless Content Updates

Update and manage content remotely for quick changes and easy control.

GOB Protected LED Modules

Encapsulated LED design helps protect against impact, dust, and handling damage.

Flexible LED Module Construction

Modular design allows for smooth curves and consistent surface flatness.

Protective Flight Case Option

Available flight case provides added protection during transport and storage.