



ServerCall Transmitter
& Cancel Panel
24 Button Panel

ServerCall®

The ServerCall Transmitter and Cancel Panel helps your kitchen manage food pick up more effectively and profitably. With the ServerCall Transmitter empower your kitchen staff to instantly notify servers when food is ready for delivery while it's hot and fresh. Add the Cancel panel to allow servers to conveniently cancel the page when the food is picked up without interrupting the kitchen workflow.

The ServerCall Transmitter and Cancel Panel are available in 12, 24, 48 or 72 button panels. With features like One-Touch Paging and Auto-Recall, you can streamline kitchen traffic and notify servers when they're needed. The ServerCall Transmitter also has programmable "Duty Alerts" for quick reminders and communication.

Additional Features

The ServerCall Transmitter supports up to 999 pagers and you can choose the type of pager that meets your needs.

UHF Technology

Up to 2-mile range with unique ID to prevent signal interference.

Auto-Recall

Automatically pages the server up to 3 times when food is ready for pick-up. The manager is automatically paged after the 3rd time to provide further assistance.

Multiple Pager and Transmitter Options

Mix and match pagers for the best solution to fit your budget and operation.

All-Page

Allows managers to quickly send a message to the entire staff for shift meetings, menu changes, etc.

Restaurant Tough

Engineered with durable plastic made to withstand the quick-service restaurant environment.

Manager Button

Instantly calls the manager to provide additional assistance as necessary.

Call today for more information

800.321.6221
www.jtech.com



ServerCall®

For the Kitchen

Specifications

Display

- > 12 / 24 / 48 / 72 Button Panel Options
- > Tri-color server lights for speed-of-service alerts
- > Dry erase panel with marker holder
- > Water-resistant polyurethane

Interfaces

- > Serial: DB9- DCE (female) Connector
- > Data Rates: 1200, 9600, 38400, 57600
- > Telco: RJ11 4-pin connector to PBX

Network

- > Interface: Ethernet 10Base-T, RJ45 connector
- > Protocols: TCP/IP, ARP, ICMP
- > Indicators (LED): Link & Activity
- > Management: SNMP, Telnet, Serial, Internal Web Server and Windows based utility for configuration

Electrical

- > Frequency range: 420 - 470 MHZ
- > FCC Identifier: QBTLTK - SCT
- > IC Identifier: 5269A - LTKSCT
- > Channel Spacing: 12.5 KHz
- > Speed / Baud Rate: 512/1200 bps

Power

- > DC 12V, 3.5A, SMPS
- > RF Output (Watts): 2 Watts
- > Format: POCSAG

Long Range Technology

- > UHF Frequency
- > Unique System ID eliminates interference
- > Up to 2-mile range

Dimensions

ServerCall Transmitter

Length: 8.26 inches (20.9 cm) Width: 14.96 inches (37.9 cm)
Height: 5.9 inches (14.9 cm) Weight: 4.28 lbs (1.9 kg)

ServerCall Options



ServerCall Transmitter
12 Button Panel



ServerCall Cancel Panel
12 Button Panel

Manager & Staff Pager Options



StaffCall IQ®



Alpha-Numeric Pager



Rugged Pager



Call today for more information
800.321.6221

JTECH

1965 Evergreen Parkway
Suite 300
Duluth, GA 30096, USA
www.jtech.com
Tel: (800) 321.6221



About JTECH Global Enterprises, Inc.

JTECH is the largest onsite paging company in the world and the leading provider of onsite messaging solutions for hospitality, healthcare, retail, church nurseries and other markets. Headquartered in Suwanee, Georgia, JTECH is an innovative technology company focused on enhancing productivity and customer service for multiple markets including restaurant and pro audio since 1971.

©2024 JTECH Company logo and product names are registered trademarks of JTECH Global Enterprises Inc. All rights reserved.