





Neo Guest Transmitter

Neo Guest Transmitter

The Neo Guest Transmitter is our most economical guest paging transmitter. It's perfect for restaurants and businesses that need a simple space-saving solution.

The Neo Guest Transmitter has up to 1 mile of site range with unique ID to prevent signal interference.

Additional Features

The Neo Guest Transmitter is perfect for smaller restaurants and businesses looking to enhance their guests' experience.

UHF Technology

Up to 1 mile site range with unique ID to prevent signal interference.

Durable

Built with high-quality materials for maximum durability and industry leading performance.

Bright LED Display

Easy-to-read LED backlit digital display. Quick buttons make repeated communications a breeze.

Smart Alerts

Out-of-Range and Search ensures guest contact and minimizes pager loss.

Manager, Staff & Guest Pagers

Supports the full line of JTECH pagers.



Neo Guest Transmitter

Easy-To-Use Transmitter

Specifications

Display	 2 x 3 inch 8 line display LED digital screen Water-resistant polyurethane
Electrical	 Frequency range: 450 - 468 MHZ FCC Identifier: WDC IC Identifier: 7752A Channel Spacing: 12.5 KHz Speed / Baud Rate: 512/1200 bps
Power	DC 12V, 3.5A, SMPSRF Output (Watts): 1 WattFormat: POCSAG
Long Range Technology	 UHF Frequency Unique System ID eliminates interference Up to 2-mile range

Dimensions

Neo Guest Transmitter	Length: 7.7 inches (19.5 cm)	Width: 4 inches (10.16 cm)
	Height: 2 inches (5 cm)	Weight: 1 lbs (0.45 k)

Works With:



GuestCall® Coaster Pager



GuestCall® CommPass



GuestCall® IQ



Rugged Pager



JTECH, an HME Company

JTECH is the largest onsite paging company in the world and the leading provider of onsite messaging solutions for hospitality, healthcare, retail, church nurseries and other markets.

© 2017 JTECH, an HME Company logo and product names are registered trademarks of HM Electronics, Inc. All rights reserved.

PS17-TXNEO-v1



